

date: 01.01.2016

uata sileet product 1002 Dolle	data sheet	product	TUBE BUTYLE
--------------------------------	------------	---------	-------------

Parameter	Value	Unit	Norm	
Elastomer base	IIR			
Geometry	Tube			
Density	1,4	g/cm³	ISO 2781	
Hardness	60 +/-5	Shore A	ISO 7619-1	
Elongation	5	MPa	NF ISO 37	
Elongation at break	420	%	NF ISO 37	
Temperature	-40 to +80	°C		
Color	white			

Specification ./.

Excellent gas permeability, good resistance to aging

Chemical resistance

Good resistant to alcohols, aldehydes, glycols, ketones, bases hypochlorides, silicone oils, vegetable oils and fats, as well as water vapor.

The values of these specifications come from regular controls of the compounds with the aid of norm samples and perform an average. They correspond to the actual state of the knowledge, the latest development of the sciences and our experience. They do not specify sure properties for the finals products. The indications in this data sheet are only a description of the typical properties and represent an aid and information for the user to give him some suggestions for his own application. But it remains in his responsibility to make sure with a specific trial that our product suits for his own purpose.

We strive to continuously improve our products. We reserve the right to modify and adjust the data sheet and our blends referring to the material properties. These will be documented with a new change status (date).